XC8-C2570 Backhoe Loader — One Machine, Two Jobs



74 kW
RATED POWER

7,600 kg
OPERATING WEIGHT

1.0 m³
BUCKET CAPACITY

4,440 mm
DIG DEPTH / DUMP HEIGHT

Overview

The XC8-C2570 does the work of an excavator and a wheel loader with one operator, one engine and one road tax disc. The front loader lifts 2,500 kg and dumps at 2,776 mm; the rear backhoe reaches 4,440 mm deep with the standard dipper (5,698 mm with the extending dipper) and swings 180° for trenching along kerbs and walls. A 74 kW Yuchai YCF36100 engine, four-wheel drive and a 38 km/h top speed make it a genuine road-going utility machine. ---

Key features

****Two machines in one**** — 1.0 m³ front bucket plus a 180° swinging backhoe, so one operator can excavate, load and backfill without a second machine.

****4,440 mm dig depth, 5,698 mm with extender**** — enough for water, gas, telecom and drainage trenches in a single pass.

****74 kW Yuchai YCF36100**** — four-cylinder turbocharged common-rail engine with 420 N·m of torque and low fuel consumption.

****38 km/h road speed with 4WD**** — travel between sites legally and quickly; 4F/3R power-shift transmission with torque converter.

****Compact road footprint**** — 7,340 × 2,350 mm body and a 5,240 mm outer turning radius for urban streets and tight sites.

****Attachment flexibility**** — front bucket, forks, 4-in-1 bucket, hammer, auger and compaction attachments extend utilisation across the year.

--

Applications

- Water, gas, telecom and power trenching
- Road repairs, kerb and verge works
- Drainage and septic installation
- Construction site loading and backfilling
- Municipal maintenance and utility fleets
- Agriculture, landscaping and rental
- --



Technical specifications

Parameter	Unit	XC8-C2570 Backhoe Loader
Operating weight	kg	**7,600**
Engine	—	**Yuchai YCF36100, 4-cyl turbo, common rail**
Displacement	L	**3.621**
Rated power	kW	**74**
Max torque	N·m	**420**
Transmission	—	**Power shift, 4 forward / 3 reverse**
Drive	—	**4WD**
Max travel speed	km/h	**38**
Overall dimensions (L×W×H)	mm	**7,340 × 2,350 × 3,437**
Wheelbase	mm	**2,180**
Min. ground clearance	mm	**318**
Outer turning radius	mm	**5,240**
Tyres (front / rear)	—	**12.5/80-18 / 19.5-24**
Loader		
Rated load	kg	**2,500**
Bucket capacity	m^3	**1.0**
Max dumping height	mm	**2,776**
Dumping reach	mm	**832**
Max breakout force	kN	**66**
Max lift force	kN	**48**
Backhoe		
Max digging depth	mm	**4,440 (5,698 with extending dipper)**
Max digging reach	mm	**6,585 (7,698 with extending dipper)**
Max digging height	mm	**6,006 (6,506 with extending dipper)**
Bucket rotation	°	**208**
Bucket digging force	kN	**63**
Dipper digging force	kN	**37**
Swing angle	°	**180**
Max traction force	kN	**≥ 70**

Standard: Yuchai YCF36100 engine, 1.0 m^3 front bucket, 4WD, power-shift transmission, ROPS/FOPS cab, front and rear work lights, road lights, tool kit.

Optional: Extending dipper, 4-in-1 front bucket, pallet forks, hydraulic breaker, auger, compaction wheel, quick coupler, air conditioning, reverse camera. ---

Get a quote for the XC8-C2570

Send your country, emission requirement and attachment list — we reply with configuration, price and shipping plan.

sales@xcmglouis.com
xcmglouis.com