XCMG MACHINES FOR EXPORT · WHEEL LOADERS

XC938 Wheel Loader — 3.5 t with 125 kN of Breakout Force



92 kW
RATED POWER

10,400 ± 200 kg
OPERATING WEIGHT

1.8 m³
BUCKET CAPACITY

2,930 mm
DIG DEPTH / DUMP HEIGHT

Overview

The XC938 fills the gap between compact 3-tonne loaders and full 5-tonne machines. Its 3,500 kg rated load and 125 kN breakout force let it attack compacted stockpiles that stop smaller loaders, while a 92 kW Weichai engine, 2,900 mm wheelbase and 10,400 kg operating weight keep it economical to run and easy to move. Bucket options from 1.8 to 3.0 m^3 cover everything from wet sand to light coal. ---

Key features

****125 kN breakout force**** — enough to dig into compacted gravel and clay without ramming the pile, cutting cycle time and tyre wear.

****92 kW Weichai engine with three-stage desert air filter**** — built for dusty quarry and yard conditions, with mechanical fuel system for easy service.

****Wide bucket range (1.8–3.0 m^3)**** — match the bucket to material density: 3.0 m^3 for coal and light grain, 1.8–2.1 m^3 for wet sand and heavy aggregate.

****Reinforced drivetrain**** — XCMG heavy-duty axles and a fixed-shaft power-shift transmission (4F/2R) for repeated loading cycles.

****Stable, comfortable platform**** — 2,900 mm wheelbase, 1,800 mm track, micro-pressurised cab with wide glass area and low noise.

****Easy maintenance**** — ground-level check points, wide-opening hood and centralized fuse box reduce daily downtime.

--

Applications

- Sand, gravel and crushed-stone quarries
- Coal yards and bulk terminals
- Ports and wharves (bulk cargo)
- Construction site loading and short-haul transfer
- Agriculture, livestock and biomass handling
- Municipal waste and snow clearing
- --



Technical specifications

Parameter	Unit	XC938 Wheel Loader
Rated load	kg	3,500
Bucket capacity	m^3	1.8 (1.8–3.0 available)
Rated power	kW	92
Operating weight	kg	10,400 ± 200
Max breakout force	kN	125 ± 5
Max tractive force	kN	100 ± 5
Wheelbase	mm	2,900
Wheel track	mm	1,800
Dumping height (standard arm)	mm	2,930
Dumping height (small-height dumping)	mm	3,200
Dumping reach	mm	1,080
Boom lifting time	s	≤ 5.0
Total cycle time	s	≤ 9
Max gradeability	°	28
Max steering angle	°	38
Speed, gear 1 (F/R)	km/h	12 / 16
Speed, gear 2 (F/R)	km/h	38 / —
Min. ground clearance	mm	365
Overall dimensions (L×W×H)	mm	7,350 × 2,482 × 3,220
Tyres	—	17.5-25

Standard: Weichai 92 kW engine, 1.8 m^3 bucket, 17.5-25 tyres, ROPS/FOPS cab, fixed-shaft power-shift transmission, load-sensing hydraulic steering, working lights.

Optional: 2.1–3.0 m^3 buckets, triple hydraulic system, pilot hydraulic control, XCMG wet axle, oil-bath air cleaner, reversing camera, centralized lubrication, high-dump and super-high-dump linkages, log/grass/fog-mouth clamps, spreader, snow shovel, quick coupler. ---

Get a quote for the XC938

Send your country, emission requirement and attachment list — we reply with configuration, price and shipping plan.

sales@xcmglouis.com
xcmglouis.com