XCMG MACHINES FOR EXPORT · CRAWLER EXCAVATORS

XE215G Crawler Excavator — The 21.5 t All-Rounder



128.5 kW
RATED POWER

21,500 kg
OPERATING WEIGHT

1.0 m³
BUCKET CAPACITY

6,156 mm
DIG DEPTH / DUMP HEIGHT

Overview

The XE215G sits in the highest-volume excavator class in the world, and it is engineered for exactly that: daily, multi-purpose work. A 128.5 kW Isuzu CC-6BG1TRP six-cylinder engine drives a positive-flow hydraulic system that delivers 149 kN of bucket digging force and smooth, predictable combined operations. With a 1.0 m³ bucket, 6,156 mm maximum digging depth and 9,940 mm reach, it handles trenching, loading, demolition and site preparation without changing class.

Key features

****Isuzu CC-6BG1TRP six-cylinder engine**** — 128.5 kW at 2,100 rpm and 637.9 N·m of torque, with the fuel tolerance and parts availability that export markets need.

****Digging performance**** — 149 kN bucket force and 110 kN arm force, matched to a 1.0 m³ bucket and a 2,910 mm arm for fast cycles in compacted material.

****Positive-flow hydraulics**** — large-displacement main pump gives fast response and high output efficiency; flow is matched to demand to cut fuel burn and heat.

****Stable, serviceable undercarriage**** — 600 mm track shoes as standard (800 mm optional), 485 mm ground clearance and a 3,363 mm track length for stability on soft ground.

****Comfortable operator station**** — ROPS/FOPS cab, suspension seat, large glass area and low in-cab noise for productive 10-hour shifts.

****Export-ready configuration**** — 21,500 kg operating weight (up to 22,500 kg in some export configurations) keeps the machine within common 3-axle low-bed limits.

--

Applications

- General building and civil construction
- Road, highway and utility trenching
- Quarry support, stockpile loading and haul-road maintenance
- Demolition and site clearance
- River dredging, irrigation and land improvement
- Rental fleets needing one machine across many job types
- --



Technical specifications

Parameter	Unit	XE215G Crawler Excavator
Operating weight	kg	**21,500 (export config. up to 22,500)**
Standard bucket capacity	m^3	**1.0 (1.05 export)**
Engine model	—	**Isuzu CC-6BG1TRP**
Cylinders	—	**6**
Rated power / speed	kW / rpm	**128.5 / 2,100**
Max torque / speed	N·m / rpm	**637.9 / 1,800**
Bucket digging force (ISO)	kN	**149**
Arm digging force (ISO)	kN	**110**
Max tractive force	kN	**184**
Travel speed (H / L)	km/h	**5.5 / 3.3**
Swing speed	rpm	**13.2**
Min. ground clearance	mm	**485**
Track shoe width	mm	**600 (800 optional)**
Max digging depth	mm	**6,156**
Max digging height	mm	**9,620**
Max dumping height	mm	**6,780**
Max digging radius	mm	**9,940**
Max ground-level digging radius	mm	**9,780**
Tail swing radius	mm	**2,890**

Standard: Isuzu CC-6BG1TRP engine, positive-flow hydraulic system, ROPS/FOPS cab with suspension seat, 1.0 m^3 bucket, 600 mm track shoes, 24 V electrics, working lights.

Optional: 800 mm track shoes, 0.9–1.2 m^3 buckets, hydraulic breaker and quick-coupler piping, long arm, air conditioning, rear-view camera, dual-fuel filtration for poor fuel quality. ---

Get a quote for the XE215G

Send your country, emission requirement and attachment list — we reply with configuration, price and shipping plan.

sales@xcmglouis.com
xcmglouis.com