

GKS32A

TELESCOPIC BOOM LIFT — **32.5 m**

OVERVIEW

The XCMG GKS32A is a telescopic boom lift from the aerial work platforms range, built for facade works, warehouse fit-out, plant maintenance, signage and lighting. Key figures: max. working height 32.5 m, max. working outreach 18 m, rated load 260 kg. Each unit is delivered with the service manual and a pre-delivery inspection report.

KEY SPECIFICATIONS

Max. working height	Max. working outreach	Rated load
32.5 m	**18 m**	**260 kg**

SPECIFICATION

Parameter	Value
Slewing angle	**±360 °**
Basket slewing angle	**±80 °**
Outreach at max. height	**32.5 m**
Height at max. outreach	**18 m**
Transport dimensions	**9880×2480×3685 L*W*H**
Chassis model	**BJ1186VKPHK-1K**
Engine model	**F4.5NS6B220**
Engine power	**162 kw**
Cab seating capacity	**3(2) persons**

TYPICAL APPLICATIONS

- facade works
- plant maintenance
- shipyards
- warehouse fit-out
- signage and lighting
- event and stadium works

Request a quotation
Specification match, landed cost and shipping plan within 24 h.

sales@xcmglouis.com
+86 516 0000 0000

Specifications are the manufacturer's published values and may change without notice. Configuration and emission standard confirmed at order.