

GKS32F

TELESCOPIC BOOM LIFT — **31.6 m**

OVERVIEW

The XCMG GKS32F is a telescopic boom lift from the aerial work platforms range, built for facade works, warehouse fit-out, plant maintenance, signage and lighting. Key figures: max. working height 31.6 m, max. working outreach 14.6 m, rated load 200 kg. Each unit is delivered with the service manual and a pre-delivery inspection report.

KEY SPECIFICATIONS

Max. working height	Max. working outreach	Rated load
31.6 m	**14.6 m**	**200 kg**

SPECIFICATION

Parameter	Value
Slewing angle	**±360 °**
Basket slewing angle	**±360 °**
Outreach at max. height	**31.6 m**
Height at max. outreach	**14.6 m**
Transport dimensions	**5005×2070×3130 L*W*H**
Chassis model	**XGA1045D6EAX**
Engine model	**D20TCIF62**
Engine power	**103 kw**
Cab seating capacity	**2 persons**

TYPICAL APPLICATIONS

- facade works
- plant maintenance
- shipyards
- warehouse fit-out
- signage and lighting
- event and stadium works

Request a quotation

Specification match, landed cost and shipping plan within 24 h.

sales@xcmglouis.com
+86 516 0000 0000

Specifications are the manufacturer's published values and may change without notice. Configuration and emission standard confirmed at order.