

GKS34AEV

TELESCOPIC BOOM LIFT

34 m

OVERVIEW

The XCMG GKS34AEV is a telescopic boom lift from the aerial work platforms range, built for facade works, warehouse fit-out, plant maintenance, signage and lighting. Key figures: max. working height 34 m, max. working outreach 19 m, rated load 260 kg. Platform height, outreach and power source are matched to your access plan.

KEY SPECIFICATIONS

Max. working height	Max. working outreach	Rated load
34 m	**19 m**	**260 kg**

SPECIFICATION

Parameter	Value
Slewing angle	**±360 °**
Basket slewing angle	**±360 °**
Outreach at max. height	**4 m**
Height at max. outreach	**22 m**
Transport dimensions	**7045×2090×3125mm**
Chassis model	**XCMG XGA1072BEVEAX**
Engine model	**TZ210XS104**
Engine power	**120kW**
Cab seating capacity	**3 persons**

TYPICAL APPLICATIONS

- facade works
- plant maintenance
- shipyards
- warehouse fit-out
- signage and lighting
- event and stadium works

Request a quotation

Specification match, landed cost and shipping plan within 24 h.

sales@xcmglouis.com
+86 516 0000 0000

Specifications are the manufacturer's published values and may change without notice. Configuration and emission standard confirmed at order.