

XCS45U 正面吊运起重机

HARBOUR MOBILE CRANE

11295 mm

OVERVIEW

The XCMG XCS45U 正面吊运起重机 is a harbour mobile crane from the cranes & lifting range, built for plant erection, steel structures, precast yards, wind farms. Key figures: overall length 11295 mm, overall width 6208 mm, overall height 4489 mm. Load charts, counterweight options and transport planning are confirmed in writing

KEY SPECIFICATIONS

Overall length	Overall width	Overall height
11295 mm	**6208 mm**	**4489 mm**

SPECIFICATION

Parameter	Value
Wheelbase	**6000 mm**
Track width	**3030/2750(front/rear) mm**
Curb weight	**70995 kg**
Unladen axle load	**33728/37267(front/rear) kg**
Engine model	**Cummins QSM11**
Engine rated power	**250 kw**
Engine rated torque	**1136 N.m**
Engine emission	**U.S.EPA Tier 3EU Stage ·**
Max. travel speed	**27/23(unladen/laden) km/h**
Min. turning diameter	**16.2 m**
Max. gradeability	**0.3**
Min. ground clearance	**400 mm**
Braking distance	**7 m**

Specifications are the manufacturer's published values and may change without notice. Configuration and emission standard confirmed at order.

Parameter	Value
Max. rated lifting capacity	**45 t**
Max. lifting height	**15100 mm**
Max. lifting speed (empty / loaded)	**350/200 m/min**
Max. lowering speed (empty / loaded)	**330/260 m/min**

TYPICAL APPLICATIONS

- plant erection
- precast yards
- bridge construction
- steel structures
- wind farms
- port handling

Request a quotation
Specification match, landed cost and shipping plan within 24 h.

sales@xcmglouis.com
+86 516 0000 0000

Specifications are the manufacturer's published values and may change without notice. Configuration and emission standard confirmed at order.