

# XGA3122BEVEA

**ELECTRIC UTILITY TRUCK** — **5995,6095,6195 *2195,2250,2300,2350,2400*2095,2135,2195,2235,2280,2350,2400 mm**

## OVERVIEW

The XCMG XGA3122BEVEA is an electric utility truck from the trucks & transport range, built for long-haul logistics, construction haulage, port drayage, mining transport. Key figures: overall dimensions 5995,6095,6195 *2195,2250,2300,2350,2400*2095,2135,2195,2235,2280,2350,2400 mm, track width (front / rear) 1680/1640 mm, wheelbase 3300 mm. Every truck ships with homologation documents and a PDI report.

## KEY SPECIFICATIONS

| Overall dimensions | Track width (front / rear) | Wheelbase |
|---|---|---|
| **5995,6095,6195 *2195,2250,·** | **1680/1640 mm** | **3300 mm** |

## SPECIFICATION

| Parameter | Value |
|---|---|
| Motor model | **TZ370XS-LKM1115** |
| Rated / peak power | **110/210 kW** |
| Rated / peak torque | **500/1100 Nm** |
| Peak speed | **4500 rpm** |
| Cooling | **Liquid cooled** |
| Rear axle model | **Hande6T** |
| Final-drive ratio | **4.875/5.571** |
| Brake type | **Air brake** |
| Drive type | **4X2** |
| Curb weight | **４６５０、４８５０、５１００ ｋｇ** |
| Max. gross weight | **11995 kg** |
| Tyre model | **235/75R17.5 18PR** |
| Battery type | **LFP (lithium iron phosphate)** |
| Battery capacity | **131.37 kW.h** |
| Front overhang | **1190** |


Specifications are the manufacturer's published values and may change without notice. Configuration and emission standard confirmed at order.

| Parameter | Value |
|---|---|
| Rear overhang | １５０５、１６０５、１７０５ |
| Top speed | **89 Km/h** |
| Cargo body dimensions | **3500,3600,3800,4000 *2000,2100,2200 *600,800 mm** |

## TYPICAL APPLICATIONS

- long-haul logistics
- port drayage
- municipal service
- construction haulage
- mining transport
- fuel and water delivery

**Request a quotation**
Specification match, landed cost and shipping plan within 24 h.
**sales@xcmglouis.com**
+86 516 0000 0000


Specifications are the manufacturer's published values and may change without notice. Configuration and emission standard confirmed at order.